

Options and accessories

Closed circuit cooling towers

Options and accessories

Below is a listing of the main HFL options and accessories. If you required option or accessory is not listed, look no further than your <u>local BAC representative</u>.



Plume abatement coil


A finned discharge coil is installed in your cooling tower discharge and piped in series with the wet coil. This reduces or eliminates plumes and extends the dry cooling capacity.



3-way-valve

A 3-way-valve is installed on your cooling tower in order to assure maximum water savings.





Sound attenuation

Reducing noise at air intake and discharge points brings us closer to silent cooling equipment.

- The sound reductions obtained by HS sound attenuation are perfect for residential sound requirements.
- Heavy noise reductions can be achieved with HD sound attenuation, making it ideal for rural requirements.



Baltiguard drive system

With this, operate your system like a dual-speed motor, but with standby reserve capacity **to cope with any failure**.



Remote sump connection

The best way to **prevent a sump freezing** is to use the auxiliary remote variety within a heated area. Shutting off the circulating pump allows all the water in the water distribution, as well as that in suspension and the sump to drain freely to the auxiliary sump.





Basin heater package

Thanks to our factory-installed heaters, the water stays at 4°C and **never freezes**, even during equipments downtime and however cold it gets outside.



Discharge hood

Discharge hoods **reduce the risk of re-circulation** in tight enclosures by increasing discharge air velocity, and can be used to elevate the unit discharge above adjacent walls to comply with layout guidelines.



Standby pump

Install a standby **reserve spray pump** as failure backup!





Steel drift eliminators

Steel drift eliminators are more **robust** than plastic alternatives.



Safety switch

Cuts power to motors with safety in mind during inspection or maintenance.



Water treatment equipment

Devices to control water treatment are needed to ensure proper **cooling tower water care**. Not only does this help protect the components and fill pack, controlling corrosion, scaling and fouling, it also avoids the proliferation of harmful bacteria, including **legionella**, in the recirculating water.





Filter

Separators and media filters efficiently **remove suspended solids** in the recirculating water, reducing system cleaning costs and optimizing water treatment results. Filtration helps you keep the recirculating water clean.



Clean out port

Clean out port makes it easy to eliminate silt and sludge from the cooling tower basin when cleaning and flushing the sump.



Flanges

Flanges facilitate **piping connections** on-site.